
## STAIRNOSING THAT MEETS INDUSTRY STANDARDS



According to SANS 10400-S:2011, 4.9.2, nosings on stairways must effectively contrast with their immediate surroundings and their minimum dimensions must be 40mm x 40mm. To ensure the safety of everyone within your space, be sure to invest in the right stairnosing products.

**K**irk upgraded their M.Trim brand single retrofit stairnosing products to meet SANS requirements. The new range is called APRN45040.N. The retrofit 45mm x 40mm aluminium base can be fitted with the following Kirk inserts:

- Smooth and Ridged PVC inserts in black, grey and brown – used in internal spaces with an average amount of wear and tear.
- Silicone Carbide Non-slip inserts in black and grey – available with or without luminescent strips. These inserts are suitable for high wear use and in areas that need to be lit during load shedding or in emergency stairwells. Suitable for internal and external use.
- Luminescent strips, which are embedded in epoxies and are slightly lower than the non-slip silicone carbide protecting the strip. Under a light source of 1000LX for 15 minutes, you get 12 hours of luminescence from the NAV720 luminescent vinyl. The SABS norm requirement is five hours.
- Diamond Rubber inserts in black suitable for internal and external applications. The rubber pyramid design provides excellent slip resistance. The infill is self-adhesive and very easy to install into the base.

For more information, contact Kirk: Tel: +27 (11) 444 1441 Website: www.kirk.co.za

